

□ Types



Pacific Marine & Industrial
www.pacificmarine.net
Info@pacificmarine.net

Construction : 6 x WS26

Rope Diameter		Minimum Breaking Load (Metric Tons)		Approx. Weight (Kg/100m)	
mm	inch	NORMAL	SUPER	NORMAL	SUPER
8		5.69	6.25	32.9	36.0
(9.53)	3/8	8.01	8.81	46.3	50.0
10		8.88	9.76	50.0	56.0
(11.11)	7/16	11.1	12.3	62.0	68.0
(12.7)	1/2	14.3	15.7	82.8	90.0
14		17.2	18.9	101.0	109.0
(14.29)	9/16	18.0	19.7	105.0	116.0
(15.88)	5/8	21.9	24.0	127.0	140.0
16		22.2	24.4	129.0	142.0
18		28.1	30.9	165.0	182.0
(19.05)	3/4	31.7	34.8	186.0	204.0
20		35.1	38.6	206.0	226.0
(22.23)	7/8	42.3	46.5	255.0	280.0
22.4		42.9	47.2	259.0	284.0
24		49.8	54.9	297.0	325.0
25		52.7	58.0	322.0	354.0
(25.4)	1	54.4	59.9	332.0	365.0
28		62.2	68.2	404.0	443.0
(28.58)	1-1/8	64.9	71.2	421.0	462.0